

# PRODUCT DATA SHEET

## SERVO PRIDE XL PLUS 15W-40



### DESCRIPTION

Servo Pride XL Plus 15W-40 is premium multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of diesel vehicles. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. This oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.

### PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Effective cam/tappet and valve train wear protection.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Has the potential of long drain interval.

### APPLICATION

Servo Pride XL Plus 15W-40 is recommended for Tata Cummins B-Series mechanical engines. The product can be used for other OEMs, new generation commercial diesel vehicles of both American and European design operating on Heavy duty on-highway and off-highway equipments.

### PERFORMANCE STANDARDS

- \* API CI-4 Plus
- \* MB 228.3
- \* VOLVO VDS-3
- \* Cummins CES 20076 / CES 20077 / CES 20078 Specs.
- \* ACEA E7

### MANUFACTURERS APPROVAL

Approved by Tata Cummins for Service Fill in Cummins B Series, BS III Mechanical Engines.

### CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14 – 15
Viscosity Index, Min.	136
TBN, mg KOH/g	9.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

### HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

**E-Mail:** [tsservices@indianoil.co.in](mailto:tsservices@indianoil.co.in) **OR** [tech\\_services@indianoil.co.in](mailto:tech_services@indianoil.co.in)

Oct-12