

PRODUCT DATA SHEET

SERVO SCOOTOMATIC 4ST



DESCRIPTION

Servo Scootomatic 4ST is high performance engine oil specially formulated for 4 stroke gearless scooters. This oil is blended from high viscosity index base stocks and contains additives to meet the performance standards for gearless scooters which is different from 4 stroke engine oil for motor cycles.

APPLICATION

Servo Scootomatic 4ST is recommended for new generation 4 stroke gearless scooters.

PERFORMANCE BENEFITS

- ☞ Superior pick up at all times
- ☞ Smooth engine performance
- ☞ Unique formulation made for modern gearless scooters.
- ☞ Enhanced engine life.
- ☞ Lower friction
- ☞ Superior thermal protection.

PERFORMANCE STANDARDS

- API SL & JASO MB

SUITABLE FOR :

- ☆ Scooters of Honda, Mahindra, TVS, Hero Honda and other reputed manufacturers.

CHARACTERISTICS

SAE GRADE	20W-40
Kin. Viscosity @ 100°C, cSt	13.5 – 15.5
Viscosity Index, Min.	110
Flash Point, COC, °C, Min	200
Pour Point, °C, Max	(-) 21
TBN, mg KOH/gm	6 - 8
Sulphated Ash % wt	0.72 – 0.90

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai - 400 051

E-Mail: servotechserv@indianoil.in **OR** servots@indianoil.in

Apr-16